WEST

Generate Collection \mathcal{IP} 8 - |274|

L8: Entry 7 of 24

File: DWPI

Jan 16, 1996

DERWENT-ACC-NO: 1996-112757

DERWENT-WEEK: 199612

COPYRIGHT 2000 DERWENT INFORMATION LTD

TITLE: Liquid epoxy! resin compsn used as impregnant for electronic parts - contg cyclohexane:di:methanol di:glycidyl:ether, acid anhydride type curing agent and curing promoter.

PATENT-ASSIGNEE:

ASSIGNEE

CODE

NEW JAPAN CHEM CO LTD

SHIV

PRIORITY-DATA:

1994JP-0152019

July 4, 1994

PATENT-FAMILY:

PUB-NO

PUB-DATE

LANGUAGE

PAGES

MAIN-IPC

JP 08012741 A

January 16, 1996

N/A

005

C08G059/20

APPLICATION-DATA:

PUB-NO

APPL-DESCRIPTOR

APPL-NO

APPL-NO

JP08012741A

July 4, 1994

1994JP-0152019

N/A

INT-CL (IPC): C08G 59/20; C08G 59/42; C08L 63/00

ABSTRACTED-PUB-NO: JP08012741A

BASIC-ABSTRACT:

A liquid epoxy resin compsn contains 100 pts wt of epoxy resin, 50-150 pts wt of (a) 1,4-cyclohexane dimethanol diglycidylether, (b) acid anhydride type curing agent whose amount is 0.8-1.1 equiv per equiv of the epoxy gp and 0.1-5 pts wt of (c) a curing promoter.

USE - Suitable as an impregnating agent for <u>electronic</u> parts, eg solenoid coil, stator of motor, insulating base film for a <u>capacitor</u>, etc.

ADVANTAGE - The resin compsn has low viscosity and good impregnating properties. The cured compsn has good head resistance, moisture resistance and electrical insulating properties.

CHOSEN-DRAWING: Dwg.0/0

TITLE-TERMS: LIQUID POLYEPOXIDE RESIN COMPOSITION IMPREGNATE ELECTRONIC PART CONTAIN CYCLOHEXANE DI METHANOL DI GLYCIDYL ETHER ACID ANHYDRIDE TYPE CURE AGENT CURE PROMOTE

DERWENT-CLASS: A21 A85 L03 V01 V02 V06 X11 X12

CPI-CODES: A05-A03; A08-D01; A08-D02; A12-E01; L03-A;

EPI-CODES: V01-B03B1; V02-E02A; V06-M08B; X11-J02B; X12-E02B;